



TYPE 2007

The road sweeper

The road sweeper ensures that the roads are maintained and kept clear, thus guaranteeing passability for vehicles and accessibility for footpaths. This makes it ideal for use in building construction, civil engineering and road construction. Using a pallet fork or quick-release plate (optional equipment), you can attach the sweeper directly to your wheel loader or skid steer loader and save the expense of purchasing a new vehicle.

CHARACTERISTICS

- ✓ fully hydraulic drive
- ✓ hydraulic lifting collecting container
- ✓ can be swiveled to the side three times
- ✓ hydraulic emptying
- ✓ quick attachment using fork mount
- ✓ hydraulic quick-release fasteners ST3
- ✓ maintenance-free
- ✓ simple operation
- ✓ oscillating sweeping roller suspension and level compensation
- ✓ fully encapsulated (low-dust)
- ✓ 4x heavy-duty wheel

SPECIAL FEATURES

- ✓ stable and robust structure for heavy-duty use
- ✓ very durable
- ✓ perfect for construction site vehicles
- ✓ the sweeper can be swiveled sideways three times without a collecting container
- ✓ ideal for use in building construction, civil engineering and road construction
- ✓ sweeping with or without dirt container possible
- ✓ quick attachment to wheel loaders or skid steer loaders using a pallet fork

CARRIER VEHICLES

For the road sweeper



Forklift



Wheel loader



Skid steer loader



Traktor

Other carrier vehicles on request.

TECHNICAL DATA

	Type 1207	Type 1507	Type 1807	Type 2007	Type 2307	Type 2507	Type 2807	Type 3007
Working width* (m) Standard: 2,0m	1,2	1,5	1,8	2,0	2,3	2,5	2,8	3,0
Weight (kg)	270	338	405	450	518	593	630	675
Dirt container (l)	240	300	360	400	460	500	560	600
Drive	fully hydr.	fully hydr.	fully hydr.	fully hydr.	fully hydr.	fully hydr.	fully hydr.	fully hydr.
Operating pressure min/max (bar)	120/240	120/240	120/240	120/240	120/240	120/240	120/240	120/240
Oil consumption min/max (l/min)	13/120	13/120	13/120	13/120	13/120	13/120	13/120	13/120
Sweeper roller trim (%)	50/50 Steel/Poly	50/50 Steel/Poly	50/50 Steel/Poly	50/50 Steel/Poly	50/50 Steel/Poly	50/50 Steel/Poly	50/50 Steel/Poly	50/50 Steel/Poly
Sweep roll diameter (mm)	600	600	600	600	600	600	600	600
Dimensions forklift pocket (mm)	135x65	135x65	135x65	135x65	135x65	135x65	135x65	135x65

* Other working widths between 1,0m – 3,0m on request.
(Information, dimensions and technical data without guarantee. Subject to change.)

SWEeper IN DETAIL

and suitable special equipment



E. g. Special equipment:
Front loader mount
Side broom
Water spraying device



E. g. Special equipment::
Front loader mount
Side broom
Water spraying device



E. g. Special equipment:
Double wheels
Side broom
Water spraying device 200l

CONTACT



MTS-Kehrmaschinen
Owner: Bernhard Roth

Adolf-Koch-Straße 8h
D - 69483 Wald-Michelbach

+49 (0) 6207 / 82847
+49 (0) 6207 / 82914
info@mts-kehrmaschinen.de
www.mts-kehrmaschinen.de